





# ADVENTURER ONE

The best car for the job is one you don't have to think about.



**Weight** 760.6 lbs (345 kg)  
**Bed capacity** 300 lbs (136 kg)  
**Tongue weight** 150 lbs (68 kg)  
**Towing capacity** 500 lbs (227 kg)

If there's one thing this Adventurer knows how to do, it's earn its keep. Sure, it may be the most comfortable, dependable utility car ever built, but it's also the least expensive to maintain. Engineered with heavy-duty features, and a powerful Yamaha engine, this hardworking vehicle can go nonstop without requiring special attention. In fact, it handles every job so well, you may forget it's there. So whether you're hauling hay, or moving dirt, this Adventurer leaves other cars in the dust.

#### EFI

Choosing Yamaha is easy when you have this kind of power. Whether you need exceptional reliability, or incredible hill-climbing ability, Yamaha makes it work for you.




#### Headlights & taillights

If the sun goes down before the work is done, no worries. The Adventurer One comes standard with bright headlights and taillights to help you find your way back to the barn.



#### 2" hitch receiver

Designed with versatility in mind, the standard 2" hitch receiver accommodates a wide variety of pull-behind accessories.





When the task at hand calls for more muscle, this big brother of the Adventurer One is exactly what you need. It's outfitted with an 800-pound payload capacity, beefed-up transaxle, four wheel drum brakes, and a reputation for being able to take on pretty much anything. Whether you're moving supplies out to the back nine, or just want to show off a bit, this crew member is the boss.



**EFI or AC**  
When the going gets tough, the tough have options. Gas or electric, Yamaha vehicles work harder and last until the job is done.



**Utility dump bed**  
With a 12.1 cubic foot, 800 lb. payload capacity, pneumatic-assist tilting, fold & lock tailgate, and roto-molded linear polyethylene construction, this is where the hard work gets done.



**Heavy duty suspension**  
We use an automotive-style, coil-over-shock strut suspension that minimizes roll, and delivers a smooth, comfortable ride. That means extra heavy-duty performance, front and rear.

# ADVENTURER TWO

Hauls everything.  
Fears nothing.



**Weight** Gas: 864.2 lbs (392 kg) Electric: 1312.8 lbs (596 kg)  
**Bed capacity** 800 lbs (363 kg)  
**Tongue weight** 150 lbs (68 kg)  
**Towing capacity** 1000 lbs (454 kg)



Sometimes the driving range can feel more like the shooting range. That's why we've outfitted our Range Picker with every piece of armor a vehicle can carry, and still be able to roll. From its strong diamond-webbed steel cage and impact resistant front windshield to its powerful engine, it is equipped with everything your crew will need to get in, get the job done, and then get right back out for more.



**Dependable 357F engine**  
Our tough, reliable, low-emission 357cc engine produces 11.4 hp of muscle. And thanks to a splash-style positive lubrication system, we've eliminated the need for an oil pump and oil filters.



**Utility dump bed**  
With a 7.8 cubic foot, 300 lb. payload capacity, pneumatic-assist tilting, fold & lock tailgate and roto-molded linear polyethylene construction, this is where the hard work gets done.



**Comfortable seats**  
The largest in the industry, featuring a polypropylene bottom that won't rot, sag, or warp. Covered with thick, durable, seamless vinyl, they're contoured for maximum comfort.

# RANGE PICKER

The only thing it doesn't do is flinch.





# FAIRWAY LOUNGE®

It's all in a day's play.

When you're the one serving up the refreshments, friends aren't the only things it's easy to make. Our Fairway Lounge allows you to cater to players' cravings right on the course, while adding to your bottom line. Let's just say it's equipped with everything you need for a moving party. More service for your members, more profit for you. In other words, this lounge is a rolling cash machine.



**Display case**  
With an attractive brushed aluminum finish, five individual storage compartments, heavy duty locking polycarbonate doors, and a locking stainless steel cash drawer, this display case is built to move product.



**Cold storage compartment**  
Hold up to 16 cases of drink cans and plenty of ice in this lockable cold storage unit. With 1.0" to 1.5" of polyurethane insulation, beverages stay nice and frosty.



**Coffee Cambro**  
Hot or cold, our beverage dispenser keeps up to 2.5 gallons of liquid ready to serve.



**Cash drawer**  
Seamlessly integrated into the display cabinet, our solid steel cash drawer can be locked or easily removed.



**Front strut-mounted cup dispenser**  
Our adjustable dispenser accommodates most conventional 6 to 10 oz. cups and can easily switch to 12 to 24 oz. cups.



**Menu board**  
Slide out design features a white board with a clear polycarbonate cover and aluminum frame. Mounts to display cabinet.



SPECIFICATIONS



ADVENTURER ONE

ADVENTURER TWO

DIMENSIONS

ELECTRIC CAR  
MOTOR/DRIVE TRAIN/  
POWER SUPPLY

GAS CAR  
ENGINE / DRIVE TRAIN

CHASSIS

PERFORMANCE

GENERAL

OVERALL LENGTH	2660 mm (104.7 in)	2922 mm (115 in)
OVERALL WIDTH	1243 mm (48.9 in)	1243 mm (48.9 in)
OVERALL HEIGHT (with suntop)	N/A	1924 mm (75.75 in)
OVERALL HEIGHT (without suntop)	1198 mm (47.2 in)	1200 mm (47.2 in)
WHEELBASE	1637 mm (64.4 in)	1917 mm (75.5 in)
FRONT WHEEL TREAD	883 mm (34.7 in)	990 mm (39 in)
REAR WHEEL TREAD	980 mm (38.6 in)	980 mm (38.6 in)
MINIMUM GROUND CLEARANCE	Gas: 112 mm (4.4 in)	Electric: 109 mm (4.2 in) Gas: 115 mm (4.5 in)
FLOOR BOARD HEIGHT	Gas: 295 mm (11.6 in)	Electric 300 mm (11.8 in) Gas: 295 mm (11.6 in)
MOTOR		48V AC
OUTPUT RATING		5.0 kW (6.7 hp) for 60 minutes
MOTOR CONTROL UNIT		NEOS 350 amp AC by TOYOTA Industrial Corporation.
BATTERIES		Eight 6-volt T-105 Batteries
CHARGER		YAMAHA-built automatic microprocessor-based high frequency switching regulated charger.
ENGINE TYPE	Single cylinder 60° incline OHV	
DISPLACEMENT	357 cc	
BORE x STROKE	85 x 63 mm	
MAXIMUM OUTPUT	8.5 kW / 3500 rpm (11.4 hp)	
COMPRESSION RATIO	8:1	
LUBRICATION SYSTEM	Splash-style positive oil lubrication	
OIL CAPACITY	1 liter, 1000 cc (1 U.S. quart)	
AIR CLEANER	Two-stage, urethane-foam pre-cleaner and high-capacity pleated paper cartridge	
COOLING SYSTEM	Forced air	
FUEL SYSTEM	Electronic fuel injection	
IGNITION SYSTEM	Transistor magneto ignition	
STARTING SYSTEM	Starter / Generator	
MAXIMUM TORQUE	25.5 Nm / 2,500 rpm	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame mated to a polypropylene structural floor. Frame is protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat	
BODY	Custom-formulated thermoplastic olefin and the front is painted with a two-part top coat of high-luster automotive-grade polyurethane.	
STEERING	Self-compensating double reduction helical rack-and-pinion, permanently lubricated with sealed bearings and greaseless tie-rod ends	
FRONT WHEEL SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension	
REAR WHEEL SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers	
BRAKES	Self adjusting mechanical rear drum	Four wheel drum brakes
SEATING	Seamless, fabric-backed vinyl bonded to pure, virgin foam contoured seat cushions and mated to a wrap and moisture-resistant polypropylene bottom, strengthened with plated steel inserts	
BUMPERS	Front and rear 5 mph energy-absorbing bumpers	
MAX FORWARD SPEED	Gas: 24 km/h (15 mph)	Electric: 31 km/h (19.0 mph) Gas: 25 km/h (15.0 mph)
MAX REVERSE SPEED	Gas: 16 km/h (10 mph)	Electric: 8.1 km/h (6 mph) Gas: 16 km/h (10 mph)
MINIMUM TURNING RADIUS	Gas: 2.8 m (9.2 ft)	Electric: 3.0 m (10.8 ft) Gas: 3.3 m (10.8 ft)
DRY WEIGHT	Gas: 345 kg (760.6 lbs)	Electric: 376 kg (827.8 lbs) w/o batteries 596 kg (1312.8 lbs) w/ 8 - 6 Volt T-105 batteries Gas: 392 kg (864.2 lbs)
CARGO BOX MATERIAL	Roto-molded linear polyethylene	
CARGO BED CAPACITY	136 kg (300 lbs)	363 kg (800 lbs)
TOWING CAPACITY	Rolling Weight: 500 lbs Towing Weight: 100 lbs	Rolling Weight: 1000 lbs Towing Weight: 150 lbs
CARGO BED SIZE (Electric)		949 mm (37.4 in) L x 1243 mm (48.9 in)W x 357 mm (14 in) H
CARGO BED SIZE (Gas)	949 mm (37.4 in) L x 1,243 mm (48.9 in) W x 357 mm (14 in) H	1209 mm (47.5 in) L x 1243 mm (48.9 in)W x 356 mm (14 in) H
CARGO BED LOAD HEIGHT	695 mm (27.3 in)	690 mm (27.1 in)
FUEL TANK CAPACITY (Gas)	22 liters (5.8 U.S. gal)	
TIRE SIZE	18 x 8.5 - 8 (4-ply rating)	Front: 18 x 8.5 - 8 (4-ply rating) Rear: 18 x 8.5 - 8 (6-ply rating)
SEATING CAPACITY	2 persons	2 persons
AVAILABLE MODEL COLORS	Standard: Tortuga Optional: Glacier, Garnet, Moonstone Metallic, Onyx Metallic, Sandstone Metallic	
AVAILABLE SEAT COLOR	Stone	
AVAILABLE SUNTOP COLOR	N/A	Black
WARRANTY	Standard 2-year limited vehicle warranty	

AVAILABLE COLORS: (Some may be Model-specific. Please see your Representative for details).

TORTUGA

GLACIER

GARNET

MOONSTONE METALLIC

ONYX METALLIC

SANDSTONE METALLIC

Custom colors available upon request.



RANGE PICKER



FAIRWAY LOUNGE

DIMENSIONS

ENGINE / DRIVE TRAIN

CHASSIS

PERFORMANCE

GENERAL

OVERALL LENGTH	2660 mm (104.7 in)	2743 mm (108 in)
OVERALL WIDTH	1295 mm (51 in)	1252 mm (49.3 in)
OVERALL HEIGHT	1702 mm (67 in) with Range Cage	1826 mm (71.9 in) with Suntop
WHEELBASE	1637 mm (64.4 in)	1917 mm (75.5 in)
FRONT WHEEL TREAD	883 mm (34.7 in)	990 mm (39 in)
REAR WHEEL TREAD	980 mm (38.6 in)	980 mm (38.6 in)
MINIMUM GROUND CLEARANCE	123 mm (4.8 in)	115 mm (4.5 in)
FLOOR BOARD HEIGHT	Electric: 342 mm (13.5 in) Gas: 295 mm (11.6 in)	295 mm (11.6 in)
ENGINE TYPE	Single cylinder 60° incline OHV	
DISPLACEMENT	357 cc	
BORE x STROKE	85 x 63 mm	
OUTPUT RATING	8.5 kW/3500 rpm (11.4 hp)	
COMPRESSION RATIO	8.1	
LUBRICATION SYSTEM	Splash-style positive oil lubrication	
OIL CAPACITY	1 liter, 1000 cc (1 U.S. quart)	
AIR CLEANER	Two-stage, urethane-foam pre-cleaner and high-capacity pleated paper cartridge	
COOLING SYSTEM	Forced air	
FUEL SYSTEM	Electronic fuel injection	
IGNITION SYSTEM	Starter / Generator	
MAXIMUM TORQUE	25.5 Nm / 2,500 rpm	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame mated to a polypropylene structural floor. Frame is protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat	
BODY	Custom-formulated thermoplastic olefin and the front is painted with a two-part top coat of high-luster automotive-grade polyurethane.	
STEERING	Self-compensating double reduction helical rack-and-pinion, permanently lubricated with sealed bearings and greaseless tie-rod ends	
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension	
REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers	
BRAKES	Mechanical 4-wheel self adjusting drum brakes	Self-adjusting, mechanical drum brakes on all 4 wheels
SEATING	Seamless, fabric-backed vinyl bonded to pure, virgin foam contoured seat cushions and mated to a wrap and moisture-resistant polypropylene bottom, strengthened with plated steel inserts	
BUMPERS	Front and rear 5 mph energy-absorbing bumpers	
MAX FORWARD SPEED	Electric: 27 km/h (17 mph)	Gas: 24 km/h (15 mph)
MAX REVERSE SPEED	Electric: 16.1 km/h (6 mph)	Gas: 16 km/h (10 mph)
MINIMUM TURNING RADIUS	Electric: 3.2 m (10.5 ft)	Gas: 3.3 m (10.8 ft)
DRY WEIGHT	Electric: 440 kg (971 lbs) with Range Cage Gas: 449 kg (990 lbs) with Range Cage	471 kg (1037.9 lbs)
CARGO CAPACITY	136 kg (300 lbs)	283.5 kg (625 lbs)
FUEL TANK CAPACITY	22 liters (5.8 U.S. gal)	
TIRE SIZE	18 x 8.5 - 8 (4-ply rating)	Front: 18 x 8.5 - 8 (4-ply rating) Rear: 18 x 8.5 - 8 (6-ply rating)
SEATING CAPACITY	2 persons	1 or 2 persons depending on vehicle configuration
AVAILABLE MODEL COLORS	Tortuga	Standard: Tortuga Optional: Glacier, Garnet, Moonstone Metallic, Onyx Metallic, Sandstone Metallic
AVAILABLE SEAT COLOR	Stone	
WARRANTY	Standard 2-year limited vehicle warranty	

Specifications subject to change without notice.

FAIRWAY LOUNGE ONLY

DISPLAY CABINET / COLD STORAGE UNIT

**Display Cabinet:** Features 5 individual storage compartments with durable locking polycarbonate doors. Cabinet has a brushed aluminum finish with a locking stainless steel cash drawer.

**Cold Storage Unit:** Features a gel-coated, UV-resistant base with 25 to 38 mm (1.0-1.5 in.) polyurethane insulated panels and a single bottom-mounted drain with shut-off valve. Holds 16 cases of canned beverages and ice.

**Cold Storage Unit Color:** Stone (standard), can be ordered to match vehicle body color.

**VEHICLE CONFIGURATIONS**

**Standard:** Adventurer Two with one bucket seat, one-piece clear windshield, Adventurer suntop and cold storage unit.

**Deluxe:** Adventurer Two with one bucket seat, one-piece clear windshield, Sunbrella canvas top, cold storage unit and display cabinet

ADDITIONAL OPTIONS

**Menu Board:** Slide out design features a white board with a clear polycarbonate cover and aluminum frame. Mounts to display cabinet

**Cambro Unit & Sweater Basket:** Cambro holds 9.5 liters (2.5 gallons) of hot or cold liquid. Sweater basket is made of heavy-gauge vinyl coated steel

**Cup Dispensers:** Two sizes to choose from. Accommodates either 6 to 10 oz. or 12 to 24 oz. cups

**Passenger Bucket Seat (N/A with Cambro Unit And Basket):** Supportive and comfortable bucket seat is made of foam in place polyurethane foam bonded to a durable vinyl cover. Available in Stone color

**Trash Receptacle:** Made of durable polyethylene with a 15 liters (4 gallons) capacity. Mounts to rear 2" hitch receiver.

STANDARD: Hunter Green. OPTIONAL: Black



See all models and accessories at  
**YAMAHAGOLFCAR.COM**  
**1.866.747.4027**



1270 Chastain Road  
Kennesaw, Georgia 30144  
1.866.747.4027  
YamahaGolfCar.com

