

COMMERCIAL LIGHT UTILITY VEHICLES



Shown with optional Yamaha Genuine Accessories.





60
+ YEARS

YAMAHA MOTOR CORPORATION

With Yamaha, every challenge is an opportunity for adventure with our rich pedigree of motor vehicles, including snowmobiles, scooters, ATVs, personal watercraft vehicles and so much more.

BOATS



MARINE ENGINES



GENERATORS



RECREATIONAL
VEHICLES



MOTORCYCLES




WAVERUNNERS®



ALL-TERRAIN
VEHICLES



SNOWMOBILES



INTELLIGENT
MACHINERY



POWER ASSIST
BICYCLES



REMOTELY PILOTED
HELICOPTERS



UMAX® CARS	4 - 17	PARTS AND ACCESSORIES	28 - 29
DRIVE² CARS	18 - 27	SPECIFICATIONS	30 - 39

Shown with optional Yamaha Genuine Accessories.

THE EASY CHOICE™ WHEN VERSATILITY, PERFORMANCE AND UTILITY MATTER.



With five color options, four-wheel brakes, luxurious bucket seats, an under-hood storage compartment and large 20" tires, all with quiet gas engines or efficient electric motors, you get the features of a hard-working utility vehicle with the feel of a golf car.



DUMP BED WITH ONE-HAND TAILGATE RELEASE

Featuring an effortless dump bed lock and tailgate, your crew members will enjoy a 12.9 cu. ft. capacity with a max load of 800lbs.



AUTOMOTIVE-STYLE DASH

Completely redesigned for today's professional with large cup holders, battery/fuel gauge, and a large storage area.



LUXURIOUS BUCKET SEATS

Derived from our award-winning Viking® Side-by-Side, you can enjoy a comfortable ride with support that will last your entire work day.

BUILD YOUR CUSTOM
UMAX WITH VIBRANT
COLOR OPTIONS



6 GLACIER



BLUESTONE

METALLIC



CARBON

METALLIC



EVERGREEN

METALLIC



CORAL RED

METALLIC 7



ALL THE POWER OF YAMAHA IN ONE CAR

GAS

FEATURES	UMAX EFI
Rear Suspension	✔ Cradle-Smooth Suspension
Front Suspension	✔ Independent Suspension
Yamaha-Built Engine	✔ 402cc, low-emission single cylinder 60° incline HOV
Miles Per Gallon	✔ 45 mpg
Vehicle Capacity	✔ 1,500 lbs
Additional Features	✔ Quiet Operation

ELECTRIC

FEATURES	UMAX Li	UMAX AC
Rear Suspension	✔ Cradle-Smooth Suspension	✔ Cradle-Smooth Suspension
Front Suspension	✔ Independent Suspension	✔ Independent Suspension
Battery	✔ Lithium-Ion	✔ 6 - 8V Trojan T-105
Toyota MCU	✔ Standard	✔ Standard
Power Production	✔ 6.7 hp (5.0 kW)	✔ 6.7 hp (5.0 kW)
Delta-Q Charger	✔ Standard	✔ Standard
Additional Features	✔ Zero Maintenance — No Watering	✔ Time Tested Reliability

Combining Yamaha's signature power and ruggedness with cutting-edge lithium technology, UMAX Li is the efficient, stress-free choice for your golf course or utility needs. With a maintenance-free* battery that's built to last, it offers greater longevity, more efficient charging, and a longer driving range to keep you going all day.

THE TRIFECTA OF SPEED, RANGE AND RELIABILITY





AVAILABLE WITH UMAX EFI AND UMAX AC POWERTRAINS

RALLY

UMAX

Our UMAX Rally® was expertly designed to get the job done, however big or small. Get the most of your work day with features like a lifted suspension, 23" tires wrapped around 12" V-window wheels and comes complete with a Yamaha Genuine front brush guard and fender flares.

A UTILITY VEHICLE WITH ATTITUDE

LIFTED
SUSPENSION

23 INCH
TIRES

6 INCH
CLEARANCE

YAMAHA



From a dirt road at the farm to a paved pathway at the airport, this vehicle ensures success. With comfortable convertible seating, plenty of storage, and an edgy design, the UMAX Rally 2+2 can fit the demands of a variety of jobs.



UMAX RALLY
STANDARD ACCESSORIES

200 LB STORAGE CAPACITY
REAR FACING FOLD-DOWN SEAT KIT



A COMFORTABLE RIDE BUILT FOR VERSATILITY

EVEN BOLDER
COLOR OPTIONS
FOR THE RALLY 2+2



16 GLACIER



BLUESTONE METALLIC



CORAL RED METALLIC



ONYX METALLIC



CYAN



CARBON METALLIC



TITAN MATTE 17

INNOVATIVE FEATURES AT EVERY TURN



With bold colors and modern body styling, our Drive² line-up looks better than ever, but the biggest change is the one you don't see—a smoother ride.

DRIVE²



STORAGE BIN AND USB CONNECTIONS

Large dash storage bin with anti-slip mat to keep valuables in place and two USB connections to maintain power and stay charged on the go.



AUTOMOTIVE-STYLE DASH

Fully equipped with larger cup holders, USB connections and ample space for mobile devices and anything else you want to take on your journey.



INDEPENDENT REAR SUSPENSION

Experience stability and comfort. Standard on all Drive² PowerTech Li, Drive² PowerTech AC and Drive² QuietTech EFI models.



GLACIER

IN-MOLD



ARCTIC DRIFT

METALLIC



CORAL RED

METALLIC



ONYX

METALLIC



PEARL

METALLIC



PERIDOT

METALLIC



CARBON

METALLIC



TITAN

MATTE

WHATEVER THE JOB, YAMAHA HAS IT COVERED



GAS

You can't go wrong with superior gas and electric solutions, all standard with independent front and rear suspension, USB ports, and padded steering wheels. If you prefer gas, the Drive² QuieTech EFI provides the quietest ride of any gas car. If you prefer electric, experience the cutting edge of lithium electric vehicles with PowerTech Li, or the time-tested batteries of the PowerTech AC. No matter the job, we'll help you get it done with complete comfort and ease.

FEATURES	DRIVE ² QUIETECH EFI
Rear Suspension	✔ Independent Suspension
Front Suspension	✔ Independent Suspension
Yamaha-Built Engine	✔ 357cc, low-emission single cylinder 60° incline HOV
Miles Per Gallon	✔ 45 mpg
Easy Access Engine Compartment	✔ Standard
Additional Features	✔ 60.5 dB engine noise

ELECTRIC

FEATURES	DRIVE ² POWERTECH Li	DRIVE ² POWERTECH AC
Rear Suspension	✔ Independent Suspension	✔ Independent Suspension
Front Suspension	✔ Independent Suspension	✔ Independent Suspension
Battery	✔ Lithium-Ion	✔ 6 - 8V Trojan T-875 FLA
Toyota MCU	✔ Standard	✔ Standard
Power Production	✔ 4.4 hp (3.3 kW)	✔ 4.4 hp (3.3 kW)
Delta-Q Charger	✔ Standard	✔ Standard
Additional Features	✔ Zero Maintenance — No Watering	✔ Time Tested Reliability

Whether you are giving a facility tour to clients or transporting guests around the hotel grounds, our Drive² Concierge 4 will always impress even the most discerning passengers. Make their first impression the best one with a smooth, quiet ride and the widest, most luxuriously comfortable seats in the industry.



EXTRA STORAGE
 UNDER TWO BENCH
 SEATS MEANS YOU'LL
 NEVER HAVE TO MAKE
 A SECOND TRIP.

CONCIERGE 6

We've outfitted both our four and six-seat Concierge models with a wealth of features to inspire the most enjoyable experiences for your riders.



SETTING THE HIGHEST STANDARD FOR COMFORT

Shown with optional Yamaha Genuine Accessories.

Where permitted by closed-community regulations or other local ordinance, the Personal Transportation Vehicle (PTV) shown is suitable for use on private/public roads with a maximum posted speed limit of 25 mph. It does not meet federal motor vehicle safety standards applicable to passenger cars.

HARDWORKING AND READY
TO HAUL ANYTHING

DRIVE^B QUIETECH EFI
POWERTECH AC
POWERTECH IRS

AVAILABLE WITH QUIETECH EFI, POWERTECH LI AND AC POWERTRAINS

Whether you're replacing water heaters or setting up for the day's big event, this extra-large hauler will handle your load. With durable, low-maintenance engineering and a super-sized aluminum cargo bed, it'll save you more than a few trips, not to mention headaches.



72" x 48"
ALUMINUM CARGO BED

800 LB
CARGO CAPACITY



DON'T EXPECT IT. DEMAND IT!®

Yamaha Genuine Parts & Accessories are backed by a factory limited warranty—up to three-years for certain Golf Car accessories. Terms and conditions apply; see your Yamaha Golf Car dealer for a copy of the limited warranty statement.



**SHOP YAMAHA
GENUINE PARTS
AND ACCESSORIES**

UMAX EFI

DIMENSIONS	
OVERALL LENGTH	119.4 in (303.0 cm)
OVERALL HEIGHT (NO SUN TOP)	48.54 in (123.3cm)
OVERALL HEIGHT (WITH SUN TOP)	71.6 in (182.5 cm)
OVERALL WIDTH	49.6 in (125.5 cm)
WHEELBASE	77.2 in (196.1 cm)
FRONT WHEEL TREAD	40.3 in (102.5 cm)
REAR WHEEL TREAD	40.2 in (102.0 cm)
MINIMUM GROUND CLEARANCE	4.5 in (11.5 cm)
CURB WEIGHT (WITH SUN TOP, BATTERY, OIL AND GASOLINE)	483 kg (1064 lb)

GENERAL	
FUEL TANK CAPACITY	5.2 US GAL (20 LITERS)
TIRE SIZE	20x10-10 4-ply Monitor K389 (front) K500 (rear)
SEATING CAPACITY	Two persons
AVAILABLE MODEL COLORS	Glacier, Coral Red, Bluestone, Carbon, Evergreen
AVAILABLE SEAT COLORS	Black
AVAILABLE SUN TOP COLORS	Black
WARRANTY	Standard 2-year limited vehicle warranty

ENGINE / DRIVE TRAIN	
ENGINE TYPE	Yamaha-built 402 cc, Low Emission Single Cylinder 60° Incline OHV
LUBRICATION SYSTEM	Splash-style positive oil lubrication
OIL CAPACITY	1.16 U.S. quart (1.1 liter, 1100 cc), Yamalube 10W-30
AIR CLEANER	Two-stage, urethane-foam pre-cleaner, and high-capacity pleated paper cartridge
COOLING SYSTEM	Forced air
FUEL SYSTEM	Electronic fuel injection
STARTING SYSTEM	Starter generator with pedal start system
HORSEPOWER	3600 rpm (14.25 hp)

CHASSIS	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with DUAL RATE coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, front and rear wheel drum brakes
CARGO BED MAX LOAD	800 lb
ROLLING TRAILER MAX WEIGHT	1,200 lb
MAX TONGUE WEIGHT	150 lb
VEHICLE RATED CAPACITY	1,500 lb
CARGO BED DIMENSIONS	41.1" L x 45.9" W x 11.8" H

PERFORMANCE	
MAX FORWARD SPEED	19.5 mph (31.4 km/h)
MAX REVERSE SPEED	13.1 mph (21 km/h)
MINIMUM TURNING RADIUS	4.0 m
G.V.W.	2,533 lb

UMAX AC

DIMENSIONS	
OVERALL LENGTH	119.4 in (303.0 cm)
OVERALL HEIGHT (NO SUN TOP)	48.54 in (123.3 cm)
OVERALL HEIGHT (WITH SUN TOP)	71.6 in (182.5 cm)
OVERALL WIDTH	49.3 in (125.5 cm)
WHEELBASE	77.2 in (196.0 cm)
FRONT WHEEL TREAD	40.3 in (102.5 cm)
REAR WHEEL TREAD	40.2 in (102.0 cm)
MINIMUM GROUND CLEARANCE	4.5 in (11.5 cm)
CURB WEIGHT (WITH SUN TOP)	658 kg (1451 lb)

GENERAL	
TIRE SIZE	20x10-10 4-ply Monitor K389 (front) K500 (rear)
SEATING CAPACITY	Two persons
AVAILABLE MODEL COLORS	Glacier, Coral Red, Bluestone, Carbon, Evergreen
AVAILABLE SEAT COLORS	Black
AVAILABLE SUN TOP COLORS	Black
WARRANTY	Standard 2-year limited vehicle warranty
STANDARD RECEIVER HITCH	2"

MOTOR / DRIVE TRAIN	
MOTOR	48-volt AC
OUTPUT RATING	6.7 hp (5.0 kW for 60 minutes)
MOTOR CONTROL UNIT	NEOS 350 amp AC controller by Toyota Industries Corporation
BATTERIES	Standard: Eight 6-volt Trojan T-105 Batteries

CHASSIS	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with DUAL RATE coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, front and rear wheel drum brakes
CARGO BED MAX LOAD	800 lb
ROLLING TRAILER MAX WEIGHT	1,200 lb
MAX TONGUE WEIGHT	150 lb
VEHICLE RATED CAPACITY	1,500 lb
CARGO BED DIMENSIONS	41.1" L x 45.9" W x 11.8" H

PERFORMANCE	
MAX FORWARD SPEED	19.5 mph (31.4 km/h)
MAX REVERSE SPEED	6.2 mph (10 km/h)
MINIMUM TURNING RADIUS	4.0 m
G.V.W.	2,910 lb

UMAX Li

DIMENSIONS	
OVERALL LENGTH	119.4 in (303.0 cm)
OVERALL HEIGHT (NO SUN TOP)	48.54 in (123.3 cm)
OVERALL HEIGHT (WITH SUN TOP)	71.6 in (182.5 cm)
OVERALL WIDTH	49.3 in (125.5 cm)
WHEELBASE	77.2 in (196.0 cm)
FRONT WHEEL TREAD	40.3 in (102.5 cm)
REAR WHEEL TREAD	40.2 in (102.0 cm)
MINIMUM GROUND CLEARANCE	4.5 in (11.5 cm)
CURB WEIGHT (WITH SUN TOP)	523 kg (1153 lb)

GENERAL	
TIRE SIZE	20x10-10 4-ply Monitor K389 (front) K500 (rear)
SEATING CAPACITY	Two persons
AVAILABLE MODEL COLORS	Coral Red, Bluestone, Evergreen, Carbon, Glacier
AVAILABLE SEAT COLORS	Black
AVAILABLE SUN TOP COLORS	Black
WARRANTY	Standard 2-year limited vehicle warranty
STANDARD RECEIVER HITCH	2"

MOTOR / DRIVE TRAIN	
MOTOR	48-volt AC
OUTPUT RATING	6.7 hp (5.0 kW for 60 minutes)
MOTOR CONTROL UNIT	NEOS 350 amp AC controller by Toyota Industries Corporation
BATTERIES	RoyPow S51105PE (51-Volt)

CHASSIS	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-gradepolyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with DUAL RATE coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, front and rear wheel drum brakes
CARGO BED MAX LOAD	800 lb
ROLLING TRAILER MAX WEIGHT	1,200 lb
MAX TONGUE WEIGHT	150 lb
VEHICLE RATED CAPACITY	1,500 lb
CARGO BED DIMENSIONS	41.1" L x 45.9" W x 11.8" H

PERFORMANCE	
MAX FORWARD SPEED	19.5 mph (31.4 km/h)
MAX REVERSE SPEED	6.2 mph (10 km/h)
MINIMUM TURNING RADIUS	4.0 m
G.V.W.	2,910 lb



RALLY EFI

DIMENSIONS	
OVERALL LENGTH	122.6 in (311.5 cm)
OVERALL HEIGHT (NO SUN TOP)	50.7 in (128.8 cm)
OVERALL HEIGHT (WITH SUN TOP)	74.0 in (188 cm)
OVERALL WIDTH	53.5 in (136 cm)
WHEELBASE	77.4 in (196.5 cm)
FRONT WHEEL TREAD	41.3 in (105.0 cm)
REAR WHEEL TREAD	41.3 in (105.0 cm)
MINIMUM GROUND CLEARANCE	5.9 in (15.0 cm)
CURB WEIGHT (WITH SUN TOP, BATTERY, OIL AND GASOLINE)	501 kg (1105 lb)
GENERAL	
FUEL TANK CAPACITY	5.2 US GAL (20 LITERS)
TIRE SIZE	23x10.5-12 4-ply Monitor K389 (front) K500 (rear)
SEATING CAPACITY	Two persons
AVAILABLE MODEL COLORS	Glacier, Coral Red, Bluestone, Carbon, Evergreen
AVAILABLE SEAT & SUN TOP COLOR	Black
WARRANTY	Standard 2-year limited vehicle warranty
STANDARD RECEIVER HITCH	2"

ENGINE / DRIVE TRAIN

ENGINE TYPE	Yamaha-built 402 cc, Low Emission Single Cylinder 60° Incline OHV
LUBRICATION SYSTEM	Splash-style positive oil lubrication
OIL CAPACITY	1.16 U.S. quart (1.1 liter, 1100 cc), Yamalube 10W-30
AIR CLEANER	Two-stage, urethane-foam pre-cleaner, and high-capacity pleated paper cartridge
COOLING SYSTEM	Forced air
FUEL SYSTEM	Electronic fuel injection
STARTING SYSTEM	Starter generator with pedal start system
HORSEPOWER	3600 rpm (14.25 hp)

CHASSIS	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with DUAL RATE coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, front and rear wheel drum brakes
CARGO BED MAX LOAD	800 lb
ROLLING TRAILER MAX WEIGHT	1,500 lb
MAX TONGUE WEIGHT	150 lb
VEHICLE RATED CAPACITY	1,500 lb
CARGO BED DIMENSIONS	41.1" L x 45.9" W x 11.8" H

PERFORMANCE	
MAX FORWARD SPEED	19.5 mph (31.4 km/h)
MAX REVERSE SPEED	13.1 mph (21 km/h)
MINIMUM TURNING RADIUS	4.0 m
G.V.W.	2,533 lb

RALLY AC

DIMENSIONS	
OVERALL LENGTH	122.5 in (311.5 cm)
OVERALL HEIGHT (NO SUN TOP)	50.7 in (128.8 cm)
OVERALL HEIGHT (WITH SUN TOP)	74.02 in (188 cm)
OVERALL WIDTH	53.5 in (136 cm)
WHEELBASE	77.3 in (196.5 cm)
FRONT WHEEL TREAD	41.3 in (104.8 cm)
REAR WHEEL TREAD	41.3 in (104.8 cm)
MINIMUM GROUND CLEARANCE	5.9 in (15.0 cm)
CURB WEIGHT (WITH SUN TOP)	676 kg (1490 lb)

GENERAL	
TIRE SIZE	23x10.5-12 4-ply Monitor K389 (front) K500 (rear)
SEATING CAPACITY	Two persons
AVAILABLE MODEL COLORS	Glacier, Coral Red, Bluestone, Carbon, Evergreen
AVAILABLE SEAT & SUN TOP COLOR	Black
WARRANTY	Standard 2-year limited vehicle warranty
STANDARD RECEIVER HITCH	2"

MOTOR / DRIVE TRAIN

MOTOR	48-volt AC
OUTPUT RATING	6.7 hp (5.0 kW)
MOTOR CONTROL UNIT	NEOS 350 amp AC controller by Toyota Industries Corporation
BATTERIES	Standard: Eight 6-volt Trojan T-105 Batteries

CHASSIS

FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with DUAL RATE coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, front and rear wheel drum brakes
CARGO BED MAX LOAD	800 lb
ROLLING TRAILER MAX WEIGHT	1,500 lb
MAX TONGUE WEIGHT	150 lb
VEHICLE RATED CAPACITY	1,500 lb
CARGO BED DIMENSIONS	41.1" L x 45.9" W x 11.8" H

PERFORMANCE	
MAX FORWARD SPEED	19.5 mph (31.4 km/h)
MAX REVERSE SPEED	6.2 mph (10 km/h)
MINIMUM TURNING RADIUS	4.0 m
G.V.W.	2,910 lb

RALLY²⁺² EFI

DIMENSIONS	
OVERALL LENGTH	134.4 in (341.5 cm)
OVERALL HEIGHT (NO SUN TOP)	57.48 in (146 cm)
OVERALL HEIGHT (WITH SUN TOP)	77.20 in (196.0 cm)
OVERALL WIDTH	53.5 in (136 cm)
WHEELBASE	77.4 in (196.5 cm)
FRONT WHEEL TREAD	41.3 in (105.0 cm)
REAR WHEEL TREAD	41.3 in (105.0 cm)
MINIMUM GROUND CLEARANCE	5.9 in (15.0 cm)
CURB WEIGHT	610 kg (1345 lb)

GENERAL	
FUEL TANK CAPACITY	5.2 US GAL (20 LITERS)
TIRE SIZE	23x10.5-12 4-ply Monitor K389 (front) K500 (rear)
SEATING CAPACITY	Four persons
AVAILABLE MODEL COLORS	Glacier, Coral Red, Bluestone, Cyan, Onyx, Carbon Matte: Titan
AVAILABLE SEAT & SUN TOP COLOR	Black
WARRANTY	Standard 2-year limited vehicle warranty

MOTOR / DRIVE TRAIN

ENGINE TYPE	Yamaha-built 402 cc, Low Emission Single Cylinder 60° Incline OHV
LUBRICATION SYSTEM	Splash-style positive oil lubrication
OIL CAPACITY	1.16 U.S. quart (1.1 liter, 1100 cc), Yamalube 10W-30
AIR CLEANER	Two-stage, urethane-foam pre-cleaner, and high-capacity pleated paper cartridge
COOLING SYSTEM	Forced air
FUEL SYSTEM	Electronic fuel injection
STARTING SYSTEM	Starter generator with pedal start system
HORSEPOWER	3600 rpm (14.25 hp)

CHASSIS	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with DUAL RATE coil springs over hydraulic shock absorbers
BRAKES	Mechanical, 4-wheel drum
FLIP-SEAT CARGO BED MAX LOAD	250 lb
MAXIMUM COMBINED LOAD WITH TWO PASSENGERS AND CARGO	400 lb
VEHICLE RATED CAPACITY	1,000 lb

PERFORMANCE	
MAX FORWARD SPEED	15 mph (24.1 km/h)
MAX REVERSE SPEED	11.2 mph (18 km/h)
MINIMUM TURNING RADIUS	4.0 m
G.V.W.	2,717 lb

RALLY²⁺² AC

DIMENSIONS	
OVERALL LENGTH	134.4 in (341.5 cm)
OVERALL HEIGHT (NO SUN TOP)	57.48 in (146 cm)
OVERALL HEIGHT (WITH SUN TOP)	77.20 in (196.0 cm)
OVERALL WIDTH	53.54 in (136 cm)
WHEELBASE	77.4 in (196.5 cm)
FRONT WHEEL TREAD	41.3 in (105.0 cm)
REAR WHEEL TREAD	41.3 in (105.0 cm)
MINIMUM GROUND CLEARANCE	5.9 in (15.0 cm)
CURB WEIGHT	779 kg (1717 lb)

GENERAL	
TIRE SIZE	23x10.5-12 4-ply Monitor K389 (front) K500 (rear)
SEATING CAPACITY	Four persons
AVAILABLE MODEL COLORS	Glacier, Coral Red, Bluestone, Cyan, Onyx, Carbon Matte: Titan
AVAILABLE SEAT & SUN TOP COLOR	Black
WARRANTY	Standard 2-year limited vehicle warranty

MOTOR / DRIVE TRAIN

MOTOR	48-volt AC
OUTPUT RATING	6.7 hp (5.0 kW for 60 minutes)
MOTOR CONTROL UNIT	NEOS 350 amp AC controller by Toyota Industries Corporation
BATTERIES	Standard: Eight 6-volt Trojan T-105 Batteries

CHASSIS

FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with DUAL RATE coil springs over hydraulic shock absorbers
BRAKES	Mechanical, 4-wheel drum
CARGO BED MAX LOAD	-
ROLLING TRAILER MAX WEIGHT	1,200 lb
MAX TONGUE WEIGHT	400 lb
VEHICLE RATED CAPACITY	1,000 lb
CARGO BED DIMENSIONS	-

PERFORMANCE	
MAX FORWARD SPEED	15 mph (24.1 km/h)
MAX REVERSE SPEED	6.2 mph (10 km/h)
MINIMUM TURNING RADIUS	4.0 m
G.V.W.	2,345 lb

SUPER HAULER QUIETECH EFI

DIMENSIONS	
OVERALL LENGTH	142.9 in (363 cm)
OVERALL WIDTH	53.5 in (136 cm)
OVERALL HEIGHT (NO SUN TOP)	48.8 in (124 cm)
WHEELBASE	98 in (249 cm)
FRONT WHEEL TREAD	34.6 in (88 cm)
REAR WHEEL TREAD	39.8 in (101 cm)
MINIMUM GROUND CLEARANCE	6.3 in (16 cm)
CURB WEIGHT (WITH BATTERY, OIL AND GASOLINE)	447 kg (985 lb)
FLOOR BOARD HEIGHT	13.4 in (34 cm)

GENERAL	
FUEL TANK CAPACITY	22 liters (5.8 gallons)
TIRE SIZE	205/65-10 4-PLY
SEATING CAPACITY	Two persons
AVAILABLE MODEL COLORS	Glacier
AVAILABLE SEAT COLORS	Standard: Black Optional: Stone
AVAILABLE SUN TOP COLOR	Standard: Black
WARRANTY	Standard 2-year limited vehicle warranty

ENGINE / DRIVE TRAIN / POWER SUPPLY	
ENGINE TYPE	Yamaha-built, 357 cc, low-emission single cylinder 60° incline OHV
LUBRICATION SYSTEM	Splash-style positive oil lubrication
OIL CAPACITY	1 U.S. quart (1 liter, 1000 cc)
AIR CLEANER	Two-stage, urethane-foam pre-cleaner, and high-capacity pleated paper cartridge
COOLING SYSTEM	Forced air
FUEL SYSTEM	Electronic Fuel Injection
STARTING SYSTEM	Starter generator with pedal start system

CHASSIS	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier color
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Fully independent automotive-style strut suspension
BRAKES	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

CARGO BED SIZE	
LENGTH	70 in (177.9 cm)
WIDTH	47 in (119.4 cm)
HEIGHT	7.8 in (20 cm)
CARGO BED CAPACITY	800 lb

PERFORMANCE	
MAX SPEED ADJUSTABLE	19 mph (31 km/h)
MINIMUM TURNING RADIUS	14.4 ft (4.4 m)

SUPER HAULER POWERTECH AC

DIMENSIONS	
OVERALL LENGTH	142.9 in (363 cm)
OVERALL WIDTH	53.5 in (136 cm)
OVERALL HEIGHT (NO SUN TOP)	48.8 in (124 cm)
WHEELBASE	98 in (249 cm)
FRONT WHEEL TREAD	34.6 in (88 cm)
REAR WHEEL TREAD	38.2 in (97 cm)
MINIMUM GROUND CLEARANCE	5.5 in (14 cm)
CURB WEIGHT (WITH BATTERY)	594 kg (1310 lb)
FLOOR BOARD HEIGHT	13 in (33 cm)

GENERAL	
TIRE SIZE	205/65-10 4-PLY
SEATING CAPACITY	Two persons
AVAILABLE MODEL COLORS	Glacier
AVAILABLE SEAT COLORS	Standard: Black Optional: Stone
AVAILABLE SUN TOP COLOR	Standard: Black
WARRANTY	Standard 2-year limited vehicle warranty

MOTOR / DRIVE TRAIN	
MOTOR	48-volt AC
OUTPUT RATING	6.7 hp (5.0 kW)
MOTOR CONTROL UNIT	NEOS 350 amp AC controller by Toyota Industries Corporation
BATTERIES	Standard: Six 8-volt Trojan T-875 Batteries Optional: Eight 6-volt Trojan T-105 Batteries

CHASSIS	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier color
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

CARGO BED SIZE	
LENGTH	70 in (177.9 cm)
WIDTH	47 in (119.4 cm)
HEIGHT	7.8 in (20 cm)
CARGO BED CAPACITY	800 lb

PERFORMANCE	
MAX SPEED ADJUSTABLE	19 mph (30.5 km/h)
MINIMUM TURNING RADIUS	14.4 ft (4.4 m)

SUPER HAULER POWERTECH Li

DIMENSIONS	
OVERALL LENGTH	142.9 in (363 cm)
OVERALL WIDTH	53.5 in (136 cm)
OVERALL HEIGHT (NO SUN TOP)	48.8 in (124 cm)
WHEELBASE	98 in (249 cm)
FRONT WHEEL TREAD	34.6 in (88 cm)
REAR WHEEL TREAD	38.2 in (97 cm)
MINIMUM GROUND CLEARANCE	5.5 in (14 cm)
CURB WEIGHT (WITH BATTERY)	594 kg (1310 lb)
FLOOR BOARD HEIGHT	13 in (33 cm)

GENERAL	
TIRE SIZE	205/65-10 4-PLY
SEATING CAPACITY	Two persons
AVAILABLE MODEL COLORS	Glacier
AVAILABLE SEAT COLORS	Standard: Black Optional: Stone
AVAILABLE SUN TOP COLOR	Standard: Black
WARRANTY	Standard 2-year limited vehicle warranty

MOTOR / DRIVE TRAIN	
MOTOR	48-volt AC
OUTPUT RATING	4.4 hp (3.3 kW)
MOTOR CONTROL UNIT	Toyota Industries-built motor controller unit
BATTERY	Lithium Iron Phosphate
CHARGER	Delta-Q Charger

CHASSIS	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier color
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

CARGO BED SIZE	
LENGTH	70 in (177.9 cm)
WIDTH	47 in (119.4 cm)
HEIGHT	7.8 in (20 cm)
CARGO BED CAPACITY	800 lb

PERFORMANCE	
MAX SPEED ADJUSTABLE	15 mph (24 km/h)
MINIMUM TURNING RADIUS	14.4 ft (4.4 m)

CONCIERGE 4 QUIETECH EFI

DIMENSIONS	
OVERALL LENGTH	127.2 in (323 cm)
OVERALL WIDTH	47.2 in (120 cm)
OVERALL HEIGHT (NO SUN TOP)	48.8 in (124 cm)
WHEELBASE	98 in (249 cm)
FRONT WHEEL TREAD	34.6 in (88 cm)
REAR WHEEL TREAD	38.2 in (97 cm)
MINIMUM GROUND CLEARANCE	5.9 in (15 cm)
CURB WEIGHT (WITH SUN TOP, BATTERY, OIL AND GASOLINE)	458 kg (1010 lb)
FLOOR BOARD HEIGHT	13.4 in (34 cm)

GENERAL	
FUEL TANK CAPACITY	22 liters (5.8 gallons)
TIRE SIZE	205/65-10 4-PLY
SEATING CAPACITY	Four persons
AVAILABLE MODEL COLORS	In-Mold: Glacier, Metallic: Peridot, Onyx, Coral Red, Carbon, Matte: Titan, Arctic Drift
AVAILABLE SEAT COLORS	Standard: Stone Optional: Black
AVAILABLE SUN TOP COLOR	Stone, Black, White
WARRANTY	Standard 2-year limited vehicle warranty

ENGINE / DRIVE TRAIN / POWER SUPPLY	
ENGINE TYPE	Yamaha-built, 357 cc, low-emission single cylinder 60° incline OHV
LUBRICATION SYSTEM	Splash-style positive oil lubrication
OIL CAPACITY	1 U.S. quart (1 liter, 1000 cc)
AIR CLEANER	Two-stage, urethane-foam pre-cleaner, and high-capacity pleated paper cartridge
COOLING SYSTEM	Forced air
FUEL SYSTEM	Electronic Fuel Injection
STARTING SYSTEM	Starter generator with pedal start system

CHASSIS	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier color. Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Fully independent automotive-style strut suspension
BRAKES	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

PERFORMANCE	
MAX FORWARD SPEED	19 mph (31 km/h)
MINIMUM TURNING RADIUS	14.4 ft (4.4 m)

CONCIERGE 4 POWERTECH AC

DIMENSIONS	
OVERALL LENGTH	127.2 in (323 cm)
OVERALL WIDTH	47.2 in (120 cm)
OVERALL HEIGHT (NO SUN TOP)	48.8 in (124 cm)
WHEELBASE	98 in (249 cm)
FRONT WHEEL TREAD	34.6 in (88 cm)
REAR WHEEL TREAD	38.2 in (97 cm)
MINIMUM GROUND CLEARANCE	5.5 in (14 cm)
DRY WEIGHT (WITH SUN TOP, FLOODED BATTERY)	564 kg (1,243 lb)
FLOOR BOARD HEIGHT	13 in (33 cm)

GENERAL

TIRE SIZE	205/65-10 4-PLY
SEATING CAPACITY	Four persons
AVAILABLE MODEL COLORS	In-Mold: Glacier, Metallic: Peridot, Onyx, Coral Red, Carbon, Matte: Titan, Arctic Drift
AVAILABLE SEAT COLORS	Standard: Stone Optional: Black
AVAILABLE SUN TOP COLOR	Stone, Black, White
WARRANTY	Standard 2-year limited vehicle warranty

ENGINE / DRIVE TRAIN

MOTOR	48-volt AC
OUTPUT RATING	6.7 hp (5.0 kW)
MOTOR CONTROL UNIT	NEOS 350 amp AC controller by Toyota Industries Corporation
BATTERIES	Standard: Six 8-volt Trojan T-875 Batteries Optional: Eight 6-volt Trojan T-105 Batteries

CHASSIS

FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier color. Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

PERFORMANCE

MAX FORWARD SPEED	19 mph (31 km/h)
MINIMUM TURNING RADIUS	14.4 ft (4.4 m)

CONCIERGE 4 POWERTECH LI

DIMENSIONS	
OVERALL LENGTH	127.2 in (323 cm)
OVERALL WIDTH	47.2 in (120 cm)
OVERALL HEIGHT (NO SUN TOP)	48.8 in (124 cm)
WHEELBASE	98 in (249 cm)
FRONT WHEEL TREAD	34.6 in (88 cm)
REAR WHEEL TREAD	38.2 in (97 cm)
MINIMUM GROUND CLEARANCE	5.5 in (14 cm)
DRY WEIGHT (WITH SUN TOP, FLOODED BATTERY)	564 kg (1,243 lb)
FLOOR BOARD HEIGHT	13 in (33 cm)

GENERAL

TIRE SIZE	205/65-10 4-PLY
SEATING CAPACITY	Four persons
AVAILABLE MODEL COLORS	In-Mold: Glacier, Metallic: Peridot, Onyx, Coral Red, Carbon, Matte: Titan, Arctic Drift
AVAILABLE SEAT COLORS	Standard: Stone Optional: Black
AVAILABLE SUN TOP COLOR	Stone, Black, White
WARRANTY	Standard 2-year limited vehicle warranty

MOTOR / DRIVE TRAIN

MOTOR	48-volt AC
OUTPUT RATING	4.4 hp (3.3 kW)
MOTOR CONTROL UNIT	Toyota Industries-built motor controller unit
BATTERY	Lithium Iron Phosphate
CHARGER	Delta-Q Charger

CHASSIS

FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier color. Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

PERFORMANCE

MAX FORWARD SPEED	15 mph (24 km/h)
MINIMUM TURNING RADIUS	14.4 ft (4.4 m)

CONCIERGE 6 QUIETECH EFI

DIMENSIONS	
OVERALL LENGTH	161 in (409 cm)
OVERALL WIDTH	47.3 in (120 cm)
OVERALL HEIGHT (NO SUN TOP)	48.8 in (124 cm)
WHEELBASE	131.9 in (335 cm)
FRONT WHEEL TREAD	34.6 in (88 cm)
REAR WHEEL TREAD	38.2 in (97 cm)
MINIMUM GROUND CLEARANCE	5.9 in (15 cm)
CURB WEIGHT (WITH SUN TOP, BATTERY, OIL AND GASOLINE)	540 kg (1190 lb)
FLOOR BOARD HEIGHT	13.4 in (34 cm)

GENERAL

FUEL TANK CAPACITY	22 liters (5.8 gallons)
TIRE SIZE	205/65-10 4-PLY
SEATING CAPACITY	Six persons
AVAILABLE MODEL COLORS	In-Mold: Glacier, Metallic: Peridot, Onyx, Coral Red, Carbon, Matte: Titan, Arctic Drift
AVAILABLE SEAT COLORS	Standard: Stone Optional: Black
AVAILABLE SUN TOP COLOR	Stone, Black, White
WARRANTY	Standard 2-year limited vehicle warranty

ENGINE / DRIVE TRAIN / POWER SUPPLY

ENGINE TYPE	Yamaha-built, 357 cc, low-emission single cylinder 60° incline OHV
LUBRICATION SYSTEM	Splash-style positive oil lubrication
OIL CAPACITY	1 U.S. quart (1 liter, 1000 cc)
AIR CLEANER	Two-stage, urethane-foam pre-cleaner, and high-capacity pleated paper cartridge
COOLING SYSTEM	Forced air
FUEL SYSTEM	Electronic Fuel Injection
STARTING SYSTEM	Starter generator with pedal start system

CHASSIS

FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier color. Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Fully independent automotive-style strut suspension
BRAKES	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

PERFORMANCE

MAX FORWARD SPEED	19 mph (31 km/h)
MINIMUM TURNING RADIUS	18.7 ft (5.7 m)

CONCIERGE 6 POWERTECH AC

DIMENSIONS	
OVERALL LENGTH	161 in (409 cm)
OVERALL WIDTH	47.2 in (120 cm)
OVERALL HEIGHT (NO SUN TOP)	48.8 in (124 cm)
WHEELBASE	131.9 in (335 cm)
FRONT WHEEL TREAD	34.6 in (88 cm)
REAR WHEEL TREAD	38.2 in (97 cm)
MINIMUM GROUND CLEARANCE	5.5 in (14 cm)
CURB WEIGHT (WITH SUN TOP, FLOODED BATTERY)	628 kg (1384 lb)
FLOOR BOARD HEIGHT	13 in (33 cm)

GENERAL

TIRE SIZE	205/65-10 4-PLY
SEATING CAPACITY	Six persons
AVAILABLE MODEL COLORS	In-Mold: Glacier, Metallic: Peridot, Onyx, Coral Red, Carbon, Matte: Titan, Arctic Drift
AVAILABLE SEAT COLORS	Standard: Stone Optional: Black
AVAILABLE SUN TOP COLOR	Stone, Black, White
WARRANTY	Standard 2-year limited vehicle warranty

ENGINE / DRIVE TRAIN

MOTOR	48-volt AC
OUTPUT RATING	6.7 hp (5.0 kW)
MOTOR CONTROL UNIT	NEOS 350 amp AC controller by Toyota Industries Corporation
BATTERIES	Standard: Six 8-volt Trojan T-875 Batteries Optional: Eight 6-volt Trojan T-105 Batteries

CHASSIS

FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier color. Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

PERFORMANCE

MAX FORWARD SPEED	19 mph (31 km/h)
MINIMUM TURNING RADIUS	18.7 ft (5.7 m)

CONCIERGE 6 POWERTECH Li

DIMENSIONS	
OVERALL LENGTH	161 in (409 cm)
OVERALL WIDTH	47.2 in (120 cm)
OVERALL HEIGHT (NO SUN TOP)	48.8 in (124 cm)
WHEELBASE	131.9 in (335 cm)
FRONT WHEEL TREAD	34.6 in (88 cm)
REAR WHEEL TREAD	38.2 in (97 cm)
MINIMUM GROUND CLEARANCE	5.5 in (14 cm)
CURB WEIGHT (WITH SUN TOP, FLOODED BATTERY)	628 kg (1384 lb)
FLOOR BOARD HEIGHT	13 in (33 cm)

GENERAL	
TIRE SIZE	205/65-10 4-PLY
SEATING CAPACITY	Six persons
AVAILABLE MODEL COLORS	In-Mold: Glacier, Metallic: Peridot, Onyx, Coral Red, Carbon, Matte: Titan, Arctic Drift
AVAILABLE SEAT COLORS	Standard: Stone Optional: Black
AVAILABLE SUN TOP COLOR	Stone, Black, White
WARRANTY	Standard 2-year limited vehicle warranty

MOTOR / DRIVE TRAIN	
MOTOR	48-volt AC
OUTPUT RATING	4.4 hp (3.3 kW)
MOTOR CONTROL UNIT	Toyota Industries-built motor controller unit
BATTERY	Lithium Iron Phosphate
CHARGER	Delta-Q Charger

CHASSIS	
FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier color. Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers
BRAKES	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

PERFORMANCE	
MAX FORWARD SPEED	15 mph (24 km/h)
MINIMUM TURNING RADIUS	18.7 ft (5.7 m)



SEE MORE ONLINE!

Scan now to view warranty information.



Shown with optional Yamaha Genuine Accessories.

Where permitted by closed-community regulations or other local ordinance, the Personal Transportation Vehicle (PTV) shown is suitable for use on private/public roads with a maximum posted speed limit of 25 mph. It does not meet federal motor vehicle safety standards applicable to passenger cars.



1270 Chastain Road NW
Kennesaw, Georgia 30144
1.866.747.4027 | [YamahaGolfCar.com](https://www.YamahaGolfCar.com)



*Scan for a digital
copy of this brochure*

This document contains many of the valuable trademarks and service marks owned and used by Yamaha throughout the world. The document may also contain references to other company, brand, and product names that may be the trademarks/service marks of their respective owners. Unless noted otherwise, these company, brand, and product names are used herein for identification purposes only, and reference to any names, marks, products, or services of third parties do not constitute or imply endorsement, sponsorship, or recommendation of the third party or the product or services. Products and specifications are subject to change without notice.