

# COMMERCIAL

LIGHT UTILITY VEHICLES



 **YAMAHA**

 **Golf Car**

Shown with optional Yamaha Genuine Accessories.

60  
+ YEARS

YAMAHA MOTOR CORPORATION

With Yamaha, every challenge is an opportunity for adventure with our rich pedigree of motor vehicles, including motorcycles, ATVs, personal watercraft vehicles and so much more.



BOATS



MARINE ENGINES



WAVERUNNERS®



MOTORCYCLES



ALL-TERRAIN VEHICLES



RECREATIONAL VEHICLES



INTELLIGENT MACHINERY



REMOTELY PILOTED HELICOPTERS



# A TOUGH LIGHT UTILITY VEHICLE DESIGNED TO MAKE THE JOB EASIER.



With five color options, four-wheel brakes, luxurious bucket seats, an under-hood storage compartment and large 20" tires, all with quiet gas engines or efficient electric motors, you get the features of a hard-working utility vehicle with the feel of a golf car.

**UMAX**



Shown with optional Yamaha Genuine Accessories.



AVAILABLE WITH UMAX EFI, UMAX AC AND UMAX Li POWERTRAINS



## DUMP BED WITH ONE-HAND TAILGATE RELEASE

Featuring an effortless dump bed lock and tailgate, your crew members will enjoy a 12.9 cu. ft. capacity with a max load of 800lbs.



## AUTOMOTIVE-STYLE DASH

Completely redesigned for today's professional with large cup holders, battery/fuel gauge, and a large storage area.



## LUXURIOUS BUCKET SEATS

Derived from our award-winning Viking® Side-by-Side, you can enjoy a comfortable ride with support that will last your entire work day.

AVAILABLE FOR  
UMAX RALLY 2+2  
UMAX RALLY  
UMAX



GLACIER

AVAILABLE FOR  
UMAX RALLY 2+2



6 CYAN

AVAILABLE FOR  
UMAX RALLY 2+2  
UMAX RALLY  
UMAX



BLUESTONE

AVAILABLE FOR  
UMAX RALLY 2+2



7 TITAN

AVAILABLE FOR  
UMAX RALLY  
UMAX



EVERGREEN

AVAILABLE FOR  
UMAX RALLY 2+2  
UMAX RALLY  
UMAX



CARBON

AVAILABLE FOR  
UMAX RALLY 2+2  
UMAX RALLY  
UMAX



CORAL RED

AVAILABLE FOR  
UMAX RALLY 2+2



ONYX



GAS

ELECTRIC

ALL THE POWER  
OF YAMAHA IN  
ONE CAR

FEATURES

- Rear Suspension
- Front Suspension
- Yamaha-Built Engine
- Miles Per Gallon
- Vehicle Capacity
- Additional Features

UMAX EFI

- ✓ Cradle-Smooth Suspension
- ✓ Independent Suspension
- ✓ 402cc, low-emission single cylinder 60° incline HOV
- ✓ 45 mpg
- ✓ 1,500 lbs
- ✓ Quiet Operation

FEATURES

- Rear Suspension
- Front Suspension
- Battery
- Toyota MCU
- Power Production
- Delta-Q Charger
- Additional Features

UMAX Li

- ✓ Cradle-Smooth Suspension
- ✓ Independent Suspension
- ✓ Lithium-Ion
- ✓ Standard
- ✓ 6.7 hp (5.0 kW)
- ✓ Standard
- ✓ Zero Maintenance — No Watering

UMAX AC

- ✓ Cradle-Smooth Suspension
- ✓ Independent Suspension
- ✓ 6 - 8V Trojan T-105
- ✓ Standard
- ✓ 6.7 hp (5.0 kW)
- ✓ Standard
- ✓ Time Tested Reliability

Our UMAX Rally® was expertly designed to get the job done, however big or small. Get the most of your work day with features like a lifted suspension and 23" tires wrapped around 12" V-window wheels, complete with a Yamaha Genuine front brush guard and fender flares.

LIFTED  
SUSPENSION

23 INCH  
TIRES

6 INCH  
CLEARANCE



COMES STANDARD WITH FRONT BRUSH GUARD AND FENDER FLARES.



NEW LITHIUM BATTERY OPTION



REDESIGNED STEERING WHEEL



NEW INTEGRATED LED BRAKE AND TAILLIGHTS

RALLY

UMAX



THE UTILITY VEHICLE WITH ATTITUDE





A COMFORTABLE RIDE  
BUILT FOR VERSATILITY

AVAILABLE WITH UMAX EFI AND UMAX LI POWERTRAINS

From a dirt road at the farm to a paved pathway at the airport, this vehicle ensures you'll get the job done. With comfortable convertible seating, plenty of storage, and an edgy design, the UMAX Rally 2+2 can meet the terrain demands wherever your work takes you.



UMAX RALLY  
STANDARD ACCESSORIES

200 LB STORAGE CAPACITY  
REAR FACING FOLD-DOWN SEAT KIT

# COMFORT AND RELIABILITY FOR EVERY TASK



At Yamaha, we're innovating to make our golf cars work harder, combining modern colors, sleek body styling, and confident performance. With convenient features, smooth independent suspension engineered for comfort and the quietest, most efficient powertrains available, our Drive<sup>2</sup> lineup looks and drives better than ever.

**DRIVE<sup>2</sup>**



Shown with optional Yamaha Genuine Accessories.



## STORAGE BIN AND USB CONNECTIONS

Large dash storage bin with anti-slip mat to keep valuables in place and two USB connections to maintain power and stay charged on the go.



## AUTOMOTIVE-STYLE DASH

Fully equipped with larger cup holders, USB connections and ample space for mobile devices and anything else you want to take on your journey.



## INDEPENDENT REAR SUSPENSION

Experience stability and comfort. Standard on all Drive<sup>2</sup> PowerTech Li, Drive<sup>2</sup> PowerTech AC and Drive<sup>2</sup> QuieTech EFI models.



GLACIER

IN-MOLD



METALLIC



RACING BLUE

METALLIC



PERIDOT

METALLIC



CORAL RED

METALLIC



CARBON

METALLIC



ONYX

METALLIC



TITAN

MATTE

# WHATEVER THE JOB, YAMAHA HAS IT COVERED



GAS			ELECTRIC		
FEATURES	DRIVE <sup>2</sup> QUIETECH EFI	FEATURES	DRIVE <sup>2</sup> POWERTECH Li	FEATURES	DRIVE <sup>2</sup> POWERTECH AC
Rear Suspension	✓ Independent Suspension	Rear Suspension	✓ Independent Suspension	✓ Independent Suspension	✓ Independent Suspension
Front Suspension	✓ Independent Suspension	Front Suspension	✓ Independent Suspension	✓ Independent Suspension	✓ Independent Suspension
Yamaha-Built Engine	✓ 357cc, low-emission single cylinder 60° incline HOV	Battery	✓ Lithium-Ion	✓ 6 - 8V Trojan T-875 FLA	✓ 6 - 8V Trojan T-875 FLA
Miles Per Gallon	✓ 45 mpg	Toyota MCU	✓ Standard	✓ Standard	✓ Standard
Easy Access Engine Compartment	✓ Standard	Power Production	✓ 4.4 hp (3.3 kW)	✓ 4.4 hp (3.3 kW)	✓ 4.4 hp (3.3 kW)
Additional Features	✓ 60.5 dB engine noise	Delta-Q Charger	✓ Standard	✓ Standard	✓ Standard
		Additional Features	✓ Zero Maintenance — No Watering		✓ Time Tested Reliability

You can't go wrong with superior gas and electric solutions, all standard with independent front and rear suspension, USB ports, and padded steering wheels. If you prefer gas, the Drive<sup>2</sup> QuieTech EFI provides the quietest ride of any gas car. If you prefer electric, experience the cutting edge of lithium electric vehicles with PowerTech Li, or the time-tested batteries of the PowerTech AC. No matter the job, we'll help you get it done with complete comfort and ease.



Compare battery options online.

Whether you are giving a facility tour to clients or transporting guests around the hotel grounds, our Drive<sup>2</sup> Concierge 4 will always impress even the most discerning passengers. Make their first impression the best one with a smooth, quiet ride and the widest, most luxuriously comfortable seats in the industry.



EXTRA STORAGE  
UNDER TWO BENCH  
SEATS MEANS YOU'LL  
NEVER HAVE TO MAKE  
A SECOND TRIP.

## CONCIERGE 6

We've outfitted both our four and six-seat Concierge models with a wealth of features to inspire the most enjoyable experiences for your riders.



SETTING THE HIGHEST  
STANDARD FOR COMFORT

Shown with optional Yamaha Genuine Accessories.

Where permitted by closed-community regulations or other local ordinance, the Personal Transportation Vehicle (PTV) shown is suitable for use on private/public roads with a maximum posted speed limit of 25 mph. It does not meet federal motor vehicle safety standards applicable to passenger cars.

# SUPER HAULER

## HARDWORKING AND READY FOR THE HAUL



QUIETECH EFI  
DRIVE<sup>8</sup>  
POWERTECH AC  
POWERTECH IRS

AVAILABLE WITH QUIETECH EFI, POWERTECH Li AND AC POWERTRAINS



72" x 48"  
ALUMINUM CARGO BED

800 LB  
CARGO CAPACITY





GENUINE  
Parts & Accessories

DON'T EXPECT IT.  
DEMAND IT!®

Yamaha Genuine Parts & Accessories are backed by a factory limited warranty—up to three-years for certain Golf Car accessories. Terms and conditions apply; see your Yamaha Golf Car dealer for a copy of the limited warranty statement.



SHOP YAMAHA  
GENUINE PARTS  
AND ACCESSORIES



## SPECIFICATIONS

### DRIVE<sup>2</sup> GAS

	SUPER HAULER QUIETECH EFI	CONCIERGE 4 QUIETECH EFI	CONCIERGE 6 QUIETECH EFI	SUPER HAULER POWERTECH AC/LI	CONCIERGE 4 POWERTECH AC/LI	CONCIERGE 6 POWERTECH AC/LI
OVERALL LENGTH	142.9 in (363 cm)	127.2 in (323 cm)	160.8 in (409 cm)	142.9 in (363 cm)	127.2 in (323 cm)	160.8 in (409 cm)
OVERALL WIDTH	53.5 in (136 cm)		47.2 in (120 cm)	53.5 in (136 cm)		47.2 in (120 cm)
OVERALL HEIGHT*	73.6 in (187 cm)		71.9 in (183 cm)	AC: 73.2 in (186 cm) Li: 73.8 in (188 cm)		AC: 71.5 in (182 cm) Li: 71.9 in (183 cm)
WHEELBASE	98 in (249 cm)	98.2 in (250 cm)	131.7 in (335 cm)	98 in (249 cm)	AC: 98 in (249 cm) Li: 98.2 in (250 cm)	AC: 131.7 in (335 cm) Li: 131.9 in (335 cm)
FRONT WHEEL TREAD			34.8 in (89 cm)		AC: 34.8 in (89 cm)	Li: 34.6 in (88 cm)
REAR WHEEL TREAD			38.4 in (98 cm)	AC: 38.4 in (98 cm) Li: 38.8 in (99 cm)	AC: 38.4 in (98 cm)	Li: 39 in (99 cm)
MINIMUM GROUND CLEARANCE			5.9 in (15 cm)		AC: 5.5 in (14 cm)	Li: 6.1 in (16 cm)
CURB WEIGHT*	986 lb (447 kg)	1,017 lb (461 kg)	1,200 lb (544 kg)	AC: 1,354 lb (614 kg) Li: 1,072 lb (486 kg)	AC: 1,252 lb (568 kg) Li: 983 lb (446 kg)	AC: 1,396 lb (633 kg) Li: 1,155 lb (524 kg)
FLOOR BOARD HEIGHT			13.2 in (34 cm)	AC: 12.8 in (33 cm) Li: 13 in (33 cm)	AC: 12.8 in (33 cm)	Li: 13.2 in (34 cm)
TIRE SIZE			205/65-10 4-PLY		205/65-10 4-PLY	
FUEL TANK CAPACITY			22 liters (5.8 gallons)		N/A	
SEATING CAPACITY	Two persons	Four persons	Six persons	Two persons	Four persons	Six persons
AVAILABLE MODEL COLORS	Glacier	In-Mold: Glacier, Metallic: Peridot, Onyx, Coral Red, Carbon, Matte: Titan	Glacier	In-Mold: Glacier, Metallic: Peridot, Onyx, Coral Red, Carbon, Matte: Titan		
AVAILABLE SEAT COLORS	Standard: Black Optional: Stone	Standard: Stone Optional: Black	Standard: Black Optional: Stone	Standard: Stone Optional: Black		
AVAILABLE SUN TOP COLORS	Black	Stone, Black, White	Black	Stone, Black, White		
WARRANTY		Standard 2-year limited vehicle warranty		Standard 2-year limited vehicle warranty		
MAX FORWARD SPEED		19 mph (30.5 km/h)		19.5 mph (31.4 km/h)		
MINIMUM TURNING RADIUS	14.4 ft (4.4 m)	18.7 ft (5.7 m)		14.4 ft (4.4 m)	18.7 ft (5.7 m)	
ENGINE TYPE (Gas)   MOTOR (Electric)		Yamaha-built 357 cc, Low Emission Single Cylinder 60° Incline OHV		48-volt AC Motor		
LUBRICATION SYSTEM		Splash-style positive oil lubrication		N/A		
OIL CAPACITY   OUTPUT RATING		1.06 U.S. quart (1 liter, 1000 cc)		6.7hp (5.0 kw)		
AIR CLEANER   MOTOR CONTROL UNIT		Two-stage, urethane-foam pre-cleaner, and high-capacity pleated paper cartridge		AC: NEOS 350 amp AC controller by Toyota Industries Corporation Li: Toyota Industries-built motor controller unit		
COOLING SYSTEM   BATTERIES		Forced air cooled		AC Standard: Six 8-volt Trojan T-875 Batteries Li: Lithium Ion Phosphate		
STARTING SYSTEM   CHARGER		Starter generator with pedal start system		Li: Delta-Q Charger		
FUEL SYSTEM		Electronic fuel injection		N/A		
FRAME		HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat		HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat		
BODY	Mold-in Polypropylene	Mold-in Polypropylene for Glacier color. Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane	Mold-in Polypropylene for Glacier color.	Mold-in Polypropylene for Glacier color. Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane		
STEERING		Self-Compensating double reduction helical rack-and-pinion		Self-Compensating double reduction helical rack-and-pinion		
FRONT SUSPENSION		Tru-Trak II™ fully independent automotive-style strut suspension		Tru-Trak II™ fully independent automotive-style strut suspension		
REAR SUSPENSION		Fully independent automotive-style strut suspension		Unit swing arm with coil springs over hydraulic shock absorbers		
BRAKES		Self-adjusting mechanical, rear-wheel drum brakes		Self-adjusting mechanical, rear-wheel drum brakes		
BUMPERS		Front and rear 5 mph energy-absorbing bumpers		Front and rear 5 mph energy-absorbing bumpers		
CARGO BED LENGTH	70.1 in (178 cm)	N/A	70.1 in (178 cm)	N/A		
CARGO BED WIDTH	47 in (120 cm)	N/A	47 in (120 cm)	N/A		
CARGO BED HEIGHT	7.9 in (20 cm)	N/A	7.9 in (20 cm)	N/A		
CARGO BED CAPACITY	800 lb (363 kg)	N/A	800 lb (363 kg)	N/A		

\*Includes suntop, battery, oil, and gasoline when applicable.

### DRIVE<sup>2</sup> ELECTRIC

## SPECIFICATIONS

### UMAX GAS

	UMAX EFI	RALLY EFI	RALLY <sup>2+2</sup> EFI	UMAX AC	UMAX Li	RALLY Li	RALLY <sup>2+2</sup> Li
OVERALL LENGTH	119.3 in (303.0 cm)	122.6 in (311.5 cm)	134.4 in (341.5 cm)	119.3 in (303.0 cm)		122.6 in (311.5 cm)	134.4 in (351.5 cm)
OVERALL WIDTH	49.4 in (125.5 cm)		53.5 in (136.0 cm)	49.4 in (125.5 cm)		53.5 in (136.0 cm)	
OVERALL HEIGHT (WITH SUN TOP)	71.9 in (182.5 cm)	74.0 in (188.0 cm)	77.4 in (196.5 cm)	71.9 in (182.5 cm)		74.0 in (188.0 cm)	76.8 in (195.0 cm)
OVERALL HEIGHT (NO SUN TOP)	48.6 in (123.5 cm)		65.4 (166.0)	48.6 in (123.5 cm)		65.4 in (166.0 cm)	
WHEELBASE	77.2 in (196.0 cm)		77.4 in (196.5 cm)	77.2 in (196.0 cm)		77.4 in (196.5 cm)	
FRONT WHEEL TREAD	40.4 in (102.5 cm)		41.3 in (105.0 cm)	40.4 in (102.5 cm)		41.3 in (105.0 cm)	
REAR WHEEL TREAD	40.2 in (102.0 cm)		41.3 in (105.0 cm)	40.2 in (102.0 cm)		41.3 in (105.0 cm)	
MINIMUM GROUND CLEARANCE	4.5 in (11.5 cm)		5.9 in (15.0 cm)	4.5 in (11.5 cm)		5.9 in (15.0 cm)	
CURB WEIGHT*	1,096 lb (497 kg)	1,188 lb (539 kg)	1,367 lb (620 kg)	1,460 lb (662 kg)	1,096 lb (497 kg)	1,184 lb (537 kg)	1,363 lb (618 kg)
TIRE SIZE	20x10-10 4-ply Monitor K389 (front) K500 (rear)		23x13.50-12 4-ply	20x10-10 4-ply Monitor		23x13.50-12 4-ply	
FUEL TANK CAPACITY		5.2 US gal (20 liters)				N/A	
SEATING CAPACITY		Two Persons	Four Persons			Two Persons	Four Persons
AVAILABLE MODEL COLORS		Glacier, Coral Red, Bluestone, Carbon, Evergreen				Glacier, Coral Red, Bluestone, Carbon, Evergreen	
AVAILABLE SEAT & SUN TOP COLOR		Black				Black	
WARRANTY		Standard 2-year limited vehicle warranty				Standard 2-year limited vehicle warranty	
MAX FORWARD SPEED		19.5 mph (31.4 km/h)				19.5 mph (31.4 km/h)	
MAX REVERSE SPEED		14.6 mph (23 km/h)				6.2 mph (10 km/h)	
MINIMUM TURNING RADIUS		13.1 ft (4.0 m)				13.1 ft (4.0 m)	
G.V.W.R.	2,225 lb (1,009 kg)	2,379 lb (1,079 kg)	2,209 lb (1,002 kg)	2,589 lb (1,174 kg)	2,225 lb (1,009 kg)	2,375 lb (1,077 kg)	2,205 lb (1,000 kg)
ENGINE TYPE (Gas)   MOTOR (Electric)		Yamaha-built 402 cc, Low Emission Single Cylinder 60° Incline OHV				48-volt AC Motor	
HORSEPOWER   OUTPUT RATING		14.25 hp (3600 rpm)				6.7 hp (5.0kw for 60 minutes)	
AIR CLEANER   MOTOR CONTROL UNIT		Two-stage, urethane-foam pre-cleaner, and high-capacity pleated paper cartridge				NEOS 350 amp AC controller by Toyota Industries Corporation	
FUEL SYSTEM   BATTERIES		Electronic fuel injection				Eight 6-volt Trojan T-105 Batteries	RoyPow S51105PC (51-volt)
STARTING SYSTEM		Electric starter/generator					N/A
COOLING SYSTEM		Forced air					N/A
LUBRICATION SYSTEM		Splash-stye positive oil lubrication					N/A
OIL CAPACITY		1.16 U.S. Quart (1.1 Liter, 1100cc), Yamalube 10W-30 or 10W-40					N/A
FRAME		HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat				HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat	
BODY		Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane				Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive-grade polyurethane	
STEERING		Self-Compensating double reduction helical rack-and-pinion				Self-Compensating double reduction helical rack-and-pinion	
FRONT SUSPENSION		Tru-Trak II™ fully independent automotive-style strut suspension				Tru-Trak II™ fully independent automotive-style strut suspension	
REAR SUSPENSION		Unit swing arm with DUAL RATE coil springs over hydraulic shock absorbers				Unit swing arm with DUAL RATE coil springs over hydraulic shock absorbers	
BRAKES		Self-adjusting mechanical, front and rear wheel drum brakes				Self-adjusting mechanical, front and rear wheel drum brakes	
CARGO BED MAX LOAD		800 lb (363 kg)	N/A			800 lb (363 kg)	N/A
MAXIMUM TOWING CAPACITY		1,500 lb (680 kg)	N/A			1,500 lb (680 kg)	N/A
MAX TONGUE WEIGHT		150 lb (68 kg)	N/A			150 lb (68 kg)	N/A
VEHICLE RATED CAPACITY	1,200 lb (544 kg)		N/A			1,200 lb (544 kg)	850 lb
CARGO BED DIMENSIONS	41.1" L x 45.9" W x 11.8" H		N/A			41.1" L x 45.9" W x 11.8" H	N/A

\*Includes suntop, battery, oil, and gasoline when applicable.



Shown with optional Yamaha Genuine Accessories



1270 Chastain Road NW  
Kennesaw, Georgia 30144  
1.866.747.4027 | [YamahaGolfCar.com](http://YamahaGolfCar.com)



Scan for a digital  
copy of this brochure

This document contains many of the valuable trademarks and service marks owned and used by Yamaha throughout the world. The document may also contain references to other company, brand, and product names that may be the trademarks/service marks of their respective owners. Unless noted otherwise, these company, brand, and product names are used herein for identification purposes only, and reference to any names, marks, products, or services of third parties do not constitute or imply endorsement, sponsorship, or recommendation of the third party or the product or services. Products and specifications are subject to change without notice.



Contract # R10-1175C



Contract # 091024-YGC



Contract # 706-23