



THE EASY CHOICE WHEN LUXURY, PERFORMANCE AND VALUE MATTER.

Sometimes the driving range can feel more like the shooting range. That's why we've outfitted our Range Picker with every piece of armor a vehicle can carry, and still be able to roll. From its strong diamond-webbed steel cage and impact resistant front windshield to its powerful engine, it is equipped with everything your crew will need to get in, get the job done, and then get right back out for more.

SPECIFICATIONS

RANGE PICKER

DIMENSIONS	OVERALL LENGTH	2660 mm (104.7 in)
	OVERALL WIDTH	1295 mm (51 in)
	OVERALL HEIGHT	1702 mm (67 in) with Range Cage
	WHEELBASE	1637 mm (64.4 in)
	FRONT WHEEL TREAD	883 mm (34.7 in)
	REAR WHEEL TREAD	980 mm (38.6 in)
	MINIMUM GROUND CLEARANCE	123 mm (4.8 in)
	FLOOR BOARD HEIGHT	295 mm (11.6 in)
ENGINE / DRIVE TRAIN	ENGINE TYPE	Single cylinder 60° incline OHV
	DISPLACEMENT	357 cc
	BORE x STROKE	85 x 63 mm
	OUTPUT RATING	8.5 kW/3500 rpm (11.4 hp)
	COMPRESSION RATIO	8.1
	LUBRICATION SYSTEM	Splash-style positive oil lubrication
	OIL CAPACITY	1 liter, 1000 cc (1 U.S. quart)
	AIR CLEANER	Two-stage, urethane-foam pre-cleaner and high-capacity pleated paper cartridge
	COOLING SYSTEM	Forced air
	FUEL SYSTEM	Electronic fuel injection
	IGNITION SYSTEM	Starter / Generator
	MAXIMUM TORQUE	25.5 Nm / 2,500 rpm
CHASSIS	FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame mated to a polypropylene structural floor. Frame is protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat
	BODY	Custom-formulated thermoplastic olefin and the front is painted with a two-part top coat of high-luster automotive-grade polyurethane.
	STEERING	Self-compensating double reduction helical rack-and-pinion, permanently lubricated with sealed bearings and greaseless tie-rod ends
	FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
	REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers
	BRAKES	Mechanical 4-wheel self adjusting drum brakes
PERFORMANCE	SEATING	Seamless, fabric-backed vinyl bonded to pure, virgin foam contoured seat cushions and mated to a wrap and moisture-resistant polypropylene bottom, strengthened with plated steel inserts
	BUMPERS	Front and rear 5 mph energy-absorbing bumpers
	MAX FORWARD SPEED	24 km/h (15 mph)
	MAX REVERSE SPEED	16 km/h (10 mph)
GENERAL	MINIMUM TURNING RADIUS	3.3 m (10.8 ft)
	DRY WEIGHT	449 kg (990 lbs) with Range Cage
	CARGO CAPACITY	136 kg (300 lbs)
	FUEL TANK CAPACITY	22 liters (5.8 U.S. gal)
	TIRE SIZE	18 x 8.5 - 8 (4-ply rating)
	SEATING CAPACITY	2 persons
	AVAILABLE MODEL COLORS	Tortuga
	AVAILABLE SEAT COLOR	Stone
	WARRANTY	Standard 2-year limited vehicle warranty

Specifications subject to change without notice.